



H24BASIC

Versatile field performance





DIMENSIONS H24BASIC

Widht/ Depth/ Height800x400x530 mm
 Weight 126 kg (without oil)

DESIGNATION

H24BASIC 9028-00-14

DIES

	PART NUMBER:
H20-10.....	9063-20-10
H20-12.....	9063-20-12
H20-14.....	9063-20-14
H20-16.....	9063-20-16
H20-19.....	9063-20-19
H20-23.....	9063-20-23
H20-27.....	9063-20-27
H20-31.....	9063-20-31
H20-36.....	9063-20-36
H20-41.....	9063-20-41
H20-47.....	9063-20-47
H20-54.....	9063-20-54

TECHNICAL DATA H24BASIC:

Capacity.....	3/16" - 1 1/2"
Crimping range	10 - 61 mm
Crimping force	1370 kN
Die Set.....	H24
Maximum travel of dies in mm*	25
Master die Diam. /Length in mm.....	84 / 80
Master die Diam. /Length in inches.....	3,31 / 3,15
Machine control	Micrometer Screw
Motor Size	3 kW
Voltage 3-phase	230 / 400 V
Voltage single phase.....	230 V
Colour.....	Black / Orange

* Max opening value added to the chosen die set size will give the actual max opening in mm for a specific die set.

Kungsvägen 22, SE-783 35 Säter, Sweden
 Phone: +46-(0)225-573 30 Fax: +46-(0)225-501 08
 info@hydroscand-machine.se www.hydroscand-machine.se

