



H32D AutoCal

Quality in focus





H32D AutoCal

H-Line Crimpers

The best solution for the user.

In the H-Line crimper design the operator is in focus. Ergonomic work positions, simple and safe operation are key features. Together with the purely technical advantages the machines are truly unique.

ADVANTAGES:

- Fast and easy operation
- Digital control
- Automatic Calibration
- Fast and easy tool change



Quality in a hose assembly is a correct crimping. Do you have a crimping machine today that has not been calibrated since you bought it? What would be the cost for bringing in a service technician to calibrate the press?

This is now a problem of the past !

With our new D AutoCal system the press warns you in intervals that calibration is needed. In a process using a hardened precision bar supplied with the crimping machine you make the calibration on site yourself. The calibration will take you about 10 seconds to perform. No training required.

This is only the beginning of the innovative design of this crimping machine.

Furthermore it has enabled us to make the crimping machine very compact in dimensions to fit on your work bench. Fast crimping cycle and many more advantages for you to discover !



Advanced and easy to use digital control

Multifunctional digital control. Faster and safer entry of crimping data. No confusing micrometer. See picture.

Crimp control is positioned on the side of the head to create an ergonomic workplace for the operator.

The custom cast hydraulic tank enables filter and other parts positions easily accessible for service.



Stand for die storage



DIMENSIONS

Widht/ Depth/ Height850x400x530 mm
 Weight 173 kg (without oil)

DESIGNATION

H32D AutoCal.....9028-00-03

DIES:

	PART NUMBER:
H32-10	9060-32-10
H32-12	9060-32-12
H32-14	9060-32-14
H32-16	9060-32-16
H32-19	9060-32-19
H32-22	9060-32-22
H32-26	9060-32-26
H32-30	9060-32-30
H32-34	9060-32-34
H32-39	9060-32-39
H32-45	9060-32-45
H32-51	9060-32-51
H32-57	9060-32-57
H32-63	9060-32-63
H32-69	9060-32-69
H32-74	9060-32-74
H32-78	9060-32-78

TECHNICAL DATA

Crimping range in mm 10 - 87 mm
 Crimping range in inch 0,39 - 3,42
 Crimping force in metric tons.....200
 Crimping force in kN 2000
 Maximum hose size in inch 2"
 Die SetH32
 Maximum travel of dies in mm.....33 mm
 Master die Diam. /Length in mm.....99 / 80
 Master die Diam. /Length in inches.....3,90 / 3,15
 Machine control Digital Control with Auto.cal.
 Motor size in kW 1 phase / 3 phase
1,5 kW / 4 kW
 Motor size in HP 1 phase / 3 phase 2,0 / 5,5
 Colour Black / Orange

Kungsvägen 22, SE-783 35 Säter, Sweden
 Phone: +46-(0)225-573 30 Fax: +46-(0)225-501 08
 info@hydroscand-machine.se www.hydroscand-machine.se

